Page 1 of 4

Product Name: WRAP SEAL® QUICK REPAIR KIT FOR PIPE LEAKS

MSDS No: 100A

#### Revision No: 8

Issue Date: 01 February 2018

### Section 1 – Company Details

Company Name: Address:

**SealXpert<sup>®</sup> Products** 53 Ubi Avenue 1, #05-25 Paya Ubi Industrial Park Singapore 408934

 Tel:
 +65 6742 4992/6742 4998

 Fax:
 +65 6749 6916

 Email:
 mailbox@sealxpert.com

### Section 2 – Composition

INGREDIENTS	CAS No	%	EXPOSURE LIMITS
Fiberglass	65997-17-3	48 - 52	10mg/m <sup>3</sup>
Polypropylene polyol diphenyl methane di-isocyanate prepolymer	9048-57-1	40 - 42	N/A
Amine catalyst	6425-39-4	1 - 5	0.051 mg/m <sup>3</sup>
Methanesulfonic acid	75-75-2	< 1	0.051 mg/m <sup>3</sup>

Source of exposure limit data – ACGIHTreshold Limit Values Abbreviations : N/A – Not Applicable

#### Section 3 – Hazards Identification

Hazards Identification: Non-hazardous Substance. Not classified as dangerous goods.

Non-Hazard classification according to the criteria of NOHSC.

Non-dangerous goods classification according to the Singapore Code for Transport of Dangerous Goods.

Human Health Hazards: May cause sensitization by contact with eye.

Safety Hazards: Avoid contact with eye.

Environmental Hazards: Non-toxic to aquatic organisms

 Other Information:
 The use of shears is recommended to remove old product from pipes so as to minimize dust formation.

### Section 4 – First Aid Measures

Inhalation:Provide fresh air. If breathing becomes difficult, call physician.Skin:S24: Avoid contact with skin.<br/>Wash thoroughly with soap and water.Eye:S25: Avoid contact with eye.<br/>S26: In case of contact with eyes, rinse immediately with plenty of water and consult a<br/>physician.Ingestion:S46: If swallowed, seek medical advice immediately and show this container or label.<br/>S2: Keep out of reach of children.<br/>Unlikely route of entry.

Page 2 of 4

## Product Name: WRAP SEAL® QUICK REPAIR KIT FOR PIPE LEAKS

MSDS No: 100A

**Revision No: 8** 

Issue Date: 01 February 2018

Section 5 – Fire Fighting Measures		
Specific Hazards:	Nil.	
Extinguishing Media:	H2O spray, foam, CO2, dry chemicals or foam	
Unsuitable Extinguishing Media:	Nil	
Protective Equipment:	Firefighters to wear self-contained breathing apparatus and full protective clothing.	
Other Information:	Keep undamaged product cool with H2O fog while fighting fire.	

#### Section 6 – Accidental Release Measures

Personal Precautions	Remove all possible sources of ignition in the surrounding area.
Environmental Precautions	Prevent from spreading or entering into drains and surface waters (e.g. lakes, ponds, ditches, rivers and streams) by using sand, earth, or other appropriate non-combustible barriers.
Clean-up Methods - Small Spillages	To minimize soil and groundwater contamination, absorb liquid with sand earth or other recommended absorbent material. Sweep up and remove to a suitable, clearly marked container for disposal in accordance with local regulations.
Clean-up Methods - Large Spillages	Prevent from spreading by making a barrier with sand, earth or other containment material. Dispose of as for small spills.
Maritime Spillages	Maritime spillages should be dealt with using a Shipboard Oil Pollution Emergency Plan (SOPEP), as required by MARPOL Annex 1 Regulation 26.
Other Information	Observe all relevant local regulations.

## Section 7 – Handling and Storage

Handling: S37/S39: Wear protective glove and safety glasse s while handling uncured product. Uncured product will adhere to clothing. Maintain high standards of personal hygiene, washing hands after coming in contact with product. S24/ S25: Avoid eye and skin contact.

S3: Store in cool, dry and well-ventilated area out of direct sunlight. Store away from all Storage: heat sources. Optimum storage conditions 4 - 30°C. For best results, rotate stock.

### Section 8 – Exposure Controls / Personal Protection

INGREDIENTS	CAS No	%	EXPOSURE LIMITS
Fiberglass	65997-17-3	48 - 52	10mg/m <sup>3</sup>
Polypropylene polyol diphenyl methane di-isocyanate prepolymer	9048-57-1	40 - 42	N/A
Amine catalyst	6425-39-4	1 - 5	0.051 mg/m <sup>3</sup>
Methanesulfonic acid	75-75-2	< 1	0.051 mg/m <sup>3</sup>
Source of expensive limit date ACCIUTree	shold Limit Values		

Source of exposure limit data – ACGIHTreshold Limit Values

Abbreviations : N/A - Not Applicable

Page 3 of 4

## Product Name: WRAP SEAL<sup>®</sup> QUICK REPAIR KIT FOR PIPE LEAKS

MSDS No: 100A Revision No: 8

vision No<sup>.</sup> 8

Issue Date: 01 February 2018

Respiratory Type:	Avoid breathing of dust, vapours, mists or spray. Where ventilation is inadequate and dusts, vapours or mists are generated the use of a respirator with filter is recommended. Filter capacity and respirator type depends on exposure levels.
Eye Protection:	S39: eye/ face protection. Non-fogging chemical safety goggles or safety glasse s with side shields.
Glove Type:	S37: Wear suitable impervious protective gloves such as PVC or Nitrile golves.
Clothing :	S36: Wear suitable impervious protective clothing.

## Section 9 – Physical and Chemical Characteristics

APPEARANCE	
Physical:	Tacky resin on a fiberglass substrate
Colour :	White or Yellowish
Odour :	Very slight
Boiling Point :	N/A
Vapour Pressure :	N/A
Vapour Density (AIR = 1) :	N/A
Solubility in Water :	Nil
Specific Gravity :	1.23 at 43°C
Melting Point :	N/A
Evaporation Rate :	N/A

## Section 10 – Stability and Reactivity

Stability:StableProducts to Avoid:NoneHazardous Reactions:NoneHazardous Decomposition:None

## Section 11 – Toxicological Information

ROUTE OF ENTRY	DESCRIPTION	MINIMUM CONCENTRATION FOR EFFECT
Inhalation	R20: Harmful by inhalation. Isocyanate vapours of uncured material below detectable limits.	N/A
Skin	R42/43: May cause sensitization by inhalation and skin contact. Contact (Employing modified human draize test): Product is neither an irritant nor an allergen. Adsorption: Acute demal LD50> 2g/kg, no reaction at this dose.	N/A
Eyes	R36/37/38: Irritating to eyes, respiratory system and skin. Avoid contact; uncured material is not expected to be irritant when used as directed	N/A
Ingestion	Oral LD50> 5g/kg; no mortalities or untoward behavious reactions observed.	N/A

Page 4 of 4

## Product Name: WRAP SEAL® QUICK REPAIR KIT FOR PIPE LEAKS

Revision No: 8

Issue Date: 01 February 2018

Carcinogenicity	
-----------------	--

MSDS No: 100A

NTP:	N/A
IARC Monographs:	N/A
OSHA Regulated:	N/A

Signs And Symptoms Of Exposure Eyes: Irritation Skin :Minor irritation

Medical Conditions Aggravated By Exposure:

Open cuts or abrasions or rashes on skin

Section	12 – Eco	logical	Information

Eco-toxicity:	Non-toxic to aquatic organisms.
---------------	---------------------------------

Floats on water. Does not contains volatile components.

Persistence/Degradability: Components are inherently biodegradable.

Bioaccumulation:

#### Section 13 – Disposal Considerations

Waste Disposal : Solid waste landfill or authorized incineration

Nil

#### Section 14 – Transport Information

**Transportation:** Not classified as Dangerous Goods and can be transported by Road, Rail and Air. The item is not restricted or not regulated as per IATA

## Section 15 – Regulatory Information

#### None known

**Mobility:** 

### Section 16 – Other Information

**Other Precautions:** Removal of old bandages with oscillating saws without adequate ventilation will potentially cause irritant dusts to be generated into atmosphere. The use of shears is recommended to remove old product from pipes so as to minimize dust formation.

#### Warning to users:

This data sheet completes the technical notices but does not supersede them. The information contained in it is grounded to the statement of our knowledge of the product concerned at the publishing date.

Moreover, user's attention should be drawn on the possible risks incurred when a product is used for other purposes than those for which it has been designed. It does not stop in any case the user knowing and following the whole regulator y texts related to his activity. He will be the sole responsible of the precautions r elated to the use of the products he knows.

The aim of the whole regulator y prescriptions mentioned is to help the receiver to fulfill his duties when using the product. This list must not be considered as exhaustive. It does not stop the user from making sure that he complies with the written obligations other than those previously cited and which rule the fact of keeping and using the product for which he is the sole responsible person.